



ACURO™



ACURO with Profibus Interface

DESCRIPTION

The Dynapar brand ACURO Absolute Encoder offers a modern full-feature design equipped with Profibus interface.

The *Acuro AI25* optical absolute industrial encoder is available in a single-turn or multi-turn version. The multi-turn design is based on a reliable high-speed gear with optical scanning and the latest generation of OptoASIC technology.

The mechanical concept is based on a double ball bearing design, which is available as a solid-shaft or hollow-shaft version in common shaft diameters.

Series AI25™

Absolute Encoder With Profibus Interface

APPLICATIONS:

Ideal for applications requiring digital feedback to be sent over an industrial bus network

- Elevators
- Machine Tool
- Assembly
- Positioning

INDUSTRIES

Manufacturing, Assembly, Material Handling and any other where precise, repeatable bidirectional position measurement is required.

FEATURES/BENEFITS

- Compact design to save valuable space
- Up to 14 Bit single-turn resolution
- 4096 revolutions of multi-turn resolution
- Short installation depth
- Safety through self-diagnostics
- Solid shaft and hollow shaft versions
- -40°C to +85°C Operating temperature
- Low power consumption
- Fast delivery of any model variant
- Additional field-bus and point-to-point interfaces available



ACURO with Profibus Interface

Series AI25

Absolute Encoder With Profibus Interface

SPECIFICATIONS*

STANDARD OPERATING CHARACTERISTICS

Single-turn Resolution: 10, 12, 13, 14 Bit
 Multi-turn Resolution: 12 bit
 Linearity: +/- 1/2 LSB
 Absolute Accuracy: ±0.01° mechanical (36 arc-sec.)
 Repeatability: ±0.002° mechanical (7.2 arc-sec.)
 Code format: Binary

ENVIRONMENTAL

Operating Temperature: -40 to 85° C
 Storage Temperature: -40 to 100° C
 Enclosure Rating: IP64 or IP67
 Shock: 1,000 m/s² (6 ms)
 Vibration: 100 m/s² (10 to 2,000 Hz)

ELECTRICAL

Connection: Bus Cover with spring terminal clamps
 Supply voltage: 10-30 VDC
 Intrinsic current consumption: 200 mA (ST), 220 mA (MT)
 Baud Rate: 12 Mbaud
 Interface: Profibus-DP, Encoder Profile
 Programmable: According to Class 2
 Special Functions: Speed, Acceleration

MECHANICAL

All Types
 Maximum shaft speed: 10,000 RPM (continuous), 12,000 RPM (peak)
 Starting torque: < 1.4 in-oz
 Bearing life:
 1 x 10¹⁰ revolutions at 35% full rated shaft load
 1 x 10⁹ revolutions at 75% full rated shaft load
 1 x 10⁸ revolutions at 100% full rated shaft load
 Weight (approx.): 350 g ST, 400 g MT

Shafted Types
 Flange configurations: Square, Clamp, Servo
 Shaft diameter: 6 mm (Servo Mount), 10 mm (Clamping Mount), 3/8" (Square Flange Mount)
 Maximum shaft load:
 6 mm shaft: 13 lb axial, 24 lb radial
 10 mm shaft: 24 lb axial, 35 lb radial
 3/8" Shaft: 24 lb axial, 35 lb radial

Hubshaft Types
 Flange configuration: Hubshaft with flexible tether
 Accepted Mating Shaft Diameter (min./max.):
 6mm (5.984/5.996); 10mm (9.980/9.995);
 12 mm (11.976/11.994); 3/8" (.3742/.3748);
 1/2" (.4991/.4997)
 Allowable Mating Shaft Movement (hubshaft only): +/- 1.5 mm axial, +/- 0.2 mm radial

* Specifications are for base models with standard features only unless otherwise noted. Specifications subject to change without notice in accordance with our DBS policy of continuous improvement. All product and brand names are trademarks of their respective owners. All rights reserved.
 Dynapar™ brand ACURO™ and AI25™ are trademarks of Danaher Industrial Controls Group. All rights reserved. © 2005 DICG Corp.
 Dynapar Brand AI25 PB Data Sheet (8/05)


Code 1: Mode	Code 2: Bits	Code 3 :Mounting	Code 4: Shaft Size	Code 5: Protocol	Code 6: Electrical	Code 7: Connector
AI25	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
AI25 Size25 Acuro Absolute Encoder	Single-Turn 0010 10 Bit 0012 12 Bit 0013 13 Bit 0014 14 Bit	Available when Code 4 is 0 or A 0 Servo* Available when Code 4 is 2 or C 1 Clamping*	w/o shaft seal (IP64) 0 6 mm 1 3/8" 2 10 mm 3 3/8" Hub Shaft 4 12 mm Hubshaft 5 1/2" Hubshaft 6 10 mm Hub Shaft	6 Profibus	2 10-30 VDC	E Bus Cover 3 Strain Relief Exits. Internal T-coupler included G Bus Cover 2 Strain Relief Exits and 1 M12, 5-Pole Connector (for Tico display). Internal T-coupler included H Bus Cover Double Conin. Internal T-coupler included
	Multi-Turn 1212 12 Bit Multi-Turn, 12 Bit Single-Turn 1213 12 Bit Multi-Turn, 13 Bit Single-Turn 1214 12 Bit Multi-Turn, 14 Bit Single-Turn	Available when Code 4 is 1 or B 2 Square flange** Available when Code 4 is 3, 4, 5 or 6 3 Hubshaft w/tether†	w/ shaft seal (IP67) A 6 mm B 3/8" C 10 mm			





Customer Service +1 800.873.8731 • Technical Support +1 800.234.8731
 www.feedbackdevices.com • www.danaherindustrialcontrols.com

Absolute Encoder With Profibus Interface



Code 3: Mounting





0
Servo



1
Clamping




2
Square Flange





3
Hubshaft w/Tether

HubShaft Diameter	Min. Shaft Length	Max. Shaft Length
10mm, 3/8"	15mm (0.59")	20mm (0.79")
12mm, 1/2"	18mm (0.71")	20mm (0.79")


Code 7: Connector




E
3 Strain Relief Exits



G
2 Strain Relief Exits
1 M12, 5-pole Connector*
*M12, 5-pole Connector used to interface Hengstler Tico 731 LCD display



H
Double Conin



Length (L) Mounting Surface to Rear For connector types E, G, H & L

Mount (Code 3)	Single-Turn	Multi-Turn
(0) Servo	63.3/2.49	72.3/2.85
(1) Clamping	62.3/2.45	71.3/2.81
(2) Square Flng	64.8/2.55	73.8/2.91
(3) Hubshaft	72.2/2.84	81.2/3.2

Headquarters: 1675 Delany Road • Gurnee, IL 60031-1282 • USA
Phone: +1 847.662.2666 • Fax: +1 847.662.6633

Satellite Locations:
North America: North Carolina, South Carolina, Connecticut, Massachusetts, New York, Canada, British Virgin Islands • Europe: United Kingdom, Italy, France, Germany, Spain, Slovakia • Latin America: Brazil • Asia: China, Japan, Korea, Singapore

Customer Service:
Tel.: +1.800.873.8731
Fax: +1.847.662.4150
dynapar.custserv@dancon.com

Technical Support
Tel.: +1.800.234.8731
Fax: +1.847.782.5277
dynapar.techsupport@dancon.com

Worldwide Brands:

Dynapar™

Eagle Signal™

Harowe™

Hengstler™

NorthStar™

Veeder-Root™



**A division of
Danaher, a
Fortune 500
company with
offices in 30
countries around
the world.**

More Available. With factories around the world, global sales and applications support, and an expansive network of distributors, we stay close to our customers - shortening lead times and fostering responsiveness. Three-day lead time is standard, with same-day shipments available on many of our products.

More Selection. We have a broad selection of controllers to meet application requirements in a variety of industries. User-configurable, accurate and flexible, with low, mid, or high level performance ranges, our controller products meet your system and budgetary requirements.

More Reliable. Our experience with more than 25,000 customers has taught us to design controllers that are reliable and durable, with quality standards that meet six sigma requirements.

For additional information or a full-line catalog, contact DICG Customer Service or visit our web site.

* Specifications are for base models with standard features only unless otherwise noted. Specifications subject to change without notice in accordance with our DBS policy of continuous improvement. All product and brand names are trademarks of their respective owners. All rights reserved.

Dynapar™ brand, ACURO™ and AI25™ are trademarks of Danaher Industrial Controls Group. All rights reserved.

© 2005 DICG Corp.

Headquarters: 1675 Delany Road • Gurnee, IL 60031-1282 • USA
Phone: +1 847.662.2666 • Fax: +1 847.662.6633

Dynapar Brand AI25 PB Data Sheet (8/05)

Satellite Locations:
North America: North Carolina, South Carolina, Connecticut, Massachusetts, New York, Canada, British Virgin Islands • Europe: United Kingdom, Italy, France, Germany, Spain, Slovakia • Latin America: Brazil • Asia: China, Japan, Korea, Singapore

Customer Service:

Tel.: +1.800.873.8731

Fax: +1.847.662.4150

dynapar.custserv@dancon.com

Technical Support

Tel.: +1.800.234.8731

Fax: +1.847.782.5277

dynapar.techsupport@dancon.com



www.feedbackdevices.com • www.danaherindustrialcontrols.com

Factory Automation Worldwide Brands: *Dynapar™* • *Eagle Signal™* • *Harowe™* • *Hengstler™* • *NorthStar™* • *Veeder-Root™*